



Free standing water heaters with heat exchanger(s)		72351C	72351HC	72352C	72352HC
CHARACTERISTICS		Enamelled	Stainless	Enamelled	Stainless
Rated volume	L.	750		1000	
Rated voltage	V	380-400V 3N~			
Rated electrical power	kW	9(3x3) / 12(3x4)			
Rated pressure	bar	6			
Maximum D.H.W. tank temperature in	°C	74			
Maximum D.H.W. tank pressure in	bar	6			
Weight when empty	kg	173	155	232	198
CONNECTIONS					
8: Recirculation	"GAS/F	3/4			
9: Hot water outlet	"GAS/F	3/4			
10: Fresh water inlet - Drain	"GAS/F	3/4			
11: Thermomanometer	-	-			
12: Flange with heating element	-	-			
DIMENSIONS					
Level A	mm	366		366	
Level C	mm	1126		1626	
Level D (when the thickness of the insulation is 70 mm)	mm	Ø990		Ø990	
Level D (when the thickness of the insulation is 100 mm)	mm	Ø1050		Ø1050	
Level H (when the thickness of the insulation is 70 mm)	mm	1670		2170	
Level H (when the thickness of the insulation is 100 mm)	mm	1740		2100	
Level K	mm	1276		1726	
Level L	mm	890		1142	