



### ENAMELED BUFFER TANKS

#### PARAMETERS

Model	...	BCE 150K60	BCE 200K60	BCE 300K	BCE 500K80	BCE 750K (BCE 750F)	BCE 1000K (BCE 1000F)	BCE 1500F	BCE 2000F
Volume range	...	150	200	300	500	750	1000	1500	2000
Energy efficiency class	...	B	B	B	B	A(C)	B(C)	C	C
Rated pressure	MPa	0,8	0,8	0,8	0,8	0,6	0,6	0,8	0,8
Standing loss	W	45	53	50	73	54(116)	77(131)	155	178
Gross weight	kg	52	60	72	124	210(182)	238(206)	367	420
Insulation type	...	Rigid foam	Rigid foam	Rigid foam	Rigid foam	Rigid foam (EPS)	Rigid foam (EPS)	EPS	EPS

#### CONNECTIONS

1: Inlet / Outlet		G1 F	G1 F	G1 F	G1 1/2 F	G2 F	G2 F	G2 F	G2 F
2: Flange		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
3: Socket for thermostat		G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F
4: Additional socket		G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F
5: Recirculation		G1 F	G1 F	G1 F	G1 1/2 F	G2 F	G2 F	G2 F	G2 F
6: Inlet / Outlet		G3/4 F	G3/4 F	G3/4 F	G1 1/4 F	G1 1/4 F	G1 1/4 F	G2 F	G2 F

#### DIMENSIONS

A	mm	210	210	210	240	365	365	385	395
C	mm	595	740	840	980	890	1090	1220	1230
D	mm	620	600	670	800	1100(1010)	1100(1010)	1250	1400
G	mm	85	75	85	80	125(80)	125(80)	100	100
H	mm	1150	1430	1605	1765	1675(1655)	2020(2000)	2210	2255
L	mm	890	1165	1315	1425	1235	1585	1765	1775
β	°	90	90	90	90	45	45	45	45